

## JMTK1404A

### Features


- Excellent  $R_{DS(ON)}$  and Low Gate Charge
- 100% UIS Tested
- 100%  $V_{DS}$  Tested
- Halogen-free; RoHS-compliant

### Applications


- Load Switch
- PWM Application
- Power Management

### Product Summary


| Parameters                     | Value | Unit |
|--------------------------------|-------|------|
| $V_{DSS}$                      | 40    | V    |
| $V_{GS(th\_Typ)}$              | 2.7   | V    |
| $I_D(@V_{GS}=10V)$             | 79    | A    |
| $R_{DS(ON\_Typ)}(@V_{GS}=10V)$ | 3.1   | mΩ   |



TO-252-3L Top View



Pin Assignment



Schematic Diagram

### Ordering Information

| Device    | Marking   | MSL | Form      | Package   | Reel(pcs) | Per Carton (pcs) |
|-----------|-----------|-----|-----------|-----------|-----------|------------------|
| JMTK1404A | JMTK1404A | 3   | Tape&Reel | TO-252-3L | 2500      | 25000            |

### Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

| Symbol         | Parameter                                     | Value                                                 | Unit             |
|----------------|-----------------------------------------------|-------------------------------------------------------|------------------|
| $V_{DS}$       | Drain-to-Source Voltage                       | 40                                                    | V                |
| $V_{GS}$       | Gate-to-Source Voltage                        | $\pm 20$                                              | V                |
| $I_D$          | Continuous Drain Current                      | $T_C = 25^\circ\text{C}$<br>$T_C = 100^\circ\text{C}$ | A                |
| $I_{DM}$       | Pulsed Drain Current <sup>(1)</sup>           | Refer to Fig.4                                        | A                |
| $E_{AS}$       | Single Pulsed Avalanche Energy <sup>(2)</sup> | 306                                                   | mJ               |
| $P_D$          | Power Dissipation                             | $T_C = 25^\circ\text{C}$<br>$T_C = 100^\circ\text{C}$ | W                |
| $T_J, T_{STG}$ | Junction & Storage Temperature Range          | -55 to 150                                            | $^\circ\text{C}$ |

### Thermal Characteristics





| Symbol | Parameter                                              | Max | Unit               |
|--------|--------------------------------------------------------|-----|--------------------|
| R      | Thermal Resistance, Junction to Ambient <sup>(3)</sup> | 39  | $^\circ\text{C/W}$ |
| R      | Thermal Resistance, Junction to Case                   | 2.5 |                    |

**Electrical Characteristics** ( $T_J = 25^\circ\text{C}$  unless otherwise specified)







| Symbol                     | Parameter                                        | Conditions                                                                                  | Min. | Typ. | Max. | Unit |
|----------------------------|--------------------------------------------------|---------------------------------------------------------------------------------------------|------|------|------|------|
| Off Characteristics        |                                                  |                                                                                             |      |      |      |      |
| V <sub>(BR)DSS</sub>       | Drain-Source Breakdown Voltage                   | I <sub>D</sub> = 250μA, V <sub>GS</sub> = 0V                                                | 40   | -    | -    | V    |
| I <sub>DSS</sub>           | Zero Gate Voltage Drain Current                  | V <sub>DS</sub> = 40V, V <sub>GS</sub> = 0V                                                 | -    | -    | 1.0  | μA   |
| I <sub>GSS</sub>           | Gate-Body Leakage Current                        | V <sub>DS</sub> = 0V, V <sub>GS</sub> = ±20V                                                | -    | -    | ±100 | nA   |
| On Characteristics         |                                                  |                                                                                             |      |      |      |      |
| V <sub>GS(th)</sub>        | Gate Threshold Voltage                           | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA                                  | 1.9  | 2.7  | 3.8  | V    |
| R <sub>DS(ON)</sub>        | Static Drain-Source ON-Resistance <sup>(4)</sup> | V <sub>GS</sub> = 10V, I <sub>D</sub> = 30A                                                 | -    | 3.1  | 4.4  | mΩ   |
| Dynamic Characteristics    |                                                  |                                                                                             |      |      |      |      |
| R <sub>g</sub>             | Gate Resistance                                  | f = 1MHz                                                                                    | -    | 1.6  | -    | Ω    |
| C <sub>iss</sub>           | Input Capacitance                                | V <sub>GS</sub> = 0V, V <sub>DS</sub> = 20V,<br>f = 1MHz                                    | 3475 | 4865 | 6567 | pF   |
| C <sub>oss</sub>           | Output Capacitance                               |                                                                                             | 370  | 518  | 700  | pF   |
| C <sub>rss</sub>           | Reverse Transfer Capacitance                     |                                                                                             | 220  | 309  | 417  | pF   |
| Q <sub>g</sub>             | Total Gate Charge                                | V <sub>GS</sub> = 0 to 10V<br>V <sub>DS</sub> = 20V, I <sub>D</sub> = 20A                   | 54   | 75   | 102  | nC   |
| Q <sub>gs</sub>            | Gate Source Charge                               |                                                                                             | 18   | 25   | 34   | nC   |
| Q <sub>gd</sub>            | Gate Drain("Miller") Charge                      |                                                                                             | 11   | 16   | 22   | nC   |
|                            |                                                  |                                                                                             |      |      |      |      |
| Switching Characteristics  |                                                  |                                                                                             |      |      |      |      |
| t <sub>d(on)</sub>         | Turn-On DelayTime                                | V <sub>GS</sub> = 10V, V <sub>DD</sub> = 20V<br>I <sub>D</sub> = 20A, R <sub>GEN</sub> = 3Ω | -    | 18   | -    | ns   |
| t <sub>r</sub>             | Turn-On Rise Time                                |                                                                                             | -    | 26   | -    | ns   |
| t <sub>d(off)</sub>        | Turn-Off DelayTime                               |                                                                                             | -    | 42   | -    | ns   |
| t <sub>f</sub>             | Turn-Off Fall Time                               |                                                                                             | -    | 13   | -    | ns   |
| Body Diode Characteristics |                                                  |                                                                                             |      |      |      |      |
| I <sub>S</sub>             | Maximum Continuous Body Diode Forward Current    |                                                                                             | -    | -    | 79   | A    |
| I <sub>SM</sub>            | Maximum Pulsed Body Diode Forward Current        |                                                                                             | -    | -    | 318  | A    |
| V <sub>SD</sub>            | Body Diode Forward Voltage                       | V <sub>GS</sub> = 0V, I <sub>S</sub> = 30A                                                  | -    |      | 1.2  | V    |
| trr                        | Body Diode Reverse Recovery Time                 | I <sub>F</sub> = 20A, di/dt = 100A/us                                                       | 20   | 28   | 38   | ns   |
| Qrr                        | Body Diode Reverse Recovery Charge               |                                                                                             | -    | 22.6 | -    | nC   |

- Notes:
1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
  2.  $E_{AS}$  condition: Starting  $T_J = 25^\circ\text{C}$ ,  $V_{DD} = 20\text{V}$ ,  $V_{GS} = 10\text{V}$ ,  $R_G = 25\text{ohm}$ ,  $L = 0.5\text{mH}$ ,  $I_{AS} = 35\text{A}$ ,  $V_{DD} = 0\text{V}$  during time in avalanche.
  3.  $R$  is measured with the device mounted on a  $1\text{inch}^2$  pad of 2oz copper FR4 PCB.
  4. Pulse Test: Pulse Width  $\leq$   $\leq 0.5\%$ .

## Typical Performance Characteristics

**Figure 1: Power De-rating**

**Figure 2: Current De-rating**

**Figure 3: Normalized Maximum Transient Thermal Impedance**

**Figure 4: Peak Current Capacity**


## Typical Performance Characteristics

**Figure 5: Output Characteristics**

**Figure 6: Typical Transfer Characteristics**

**Figure 7: On-resistance vs. Drain Current**

**Figure 8: Body Diode Characteristics**

**Figure 9: Gate Charge Characteristics**

**Figure 10: Capacitance Characteristics**


## Typical Performance Characteristics



## Test Circuit



Figure 1: Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveform




Figure 3: Unclamped Inductive Switching Test Circuit & Waveform






Figure 4: Diode Recovery Test Circuit & Waveform

## Package Mechanical Data(TO-252-3L)



### Recommended Soldering Footprint



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.



is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.